

High Speed Horizontal Servo Flow Wrapper



Features

- ▶ 3 axes Servo driving system : End sealing until, Film transportation and feeding chain are driven by servo motors independently is durable, high productivity and low noise.
- ▶ User- friendly human / machine interface control with 8.4 inch dialogue type colorful monitor.

- ▶ 50 sets of recipe (bag length, feeding position, cutting position) enable product switch by one click.
- ▶ Self-diagnosis function, error message will shown on screen for easy troubleshooting.
- ▶ Four sets of temperature controllers (Japan Brand) with PID function.
- ▶ Overload sensing function for each servo motor prevents the parts and product from being damaged in advance.
- ▶ For 24 hours nonstop high speed packaging by the servomotors and timing belts driving system.

Model	HP-350-3V	HP-450-3V	HP-600-3V
Operating Speed	20 - 300 pack/min	20 - 300 pack/min	20 - 250 pack/min
Bag length	50 - 750 mm	50 - 750 mm	50 - 750 mm
Max. Film Width (max. roll dia.)	350 mm (300 mm)	450 mm (300 mm)	600 mm (350 mm)
Product Width (max.)	20 - 120 mm (50 - 150 mm)	20 - 120 mm (50 - 150 mm)	80 - 230 mm (110 - 270 mm)
Product Height	Max. 60 mm (90 mm)	Max. 60 mm (90 mm)	Max. 60 mm (110 mm)
Machine Dimensions (W x L x H)	3860 x 940 x 1560 mm	3860 x 1000 x 1560 mm	3860 x 1130 x 1560 mm



บริษัท กู๊ดไทม์ อิมพอร์ต เอ็กซ์พอร์ต จำกัด
16 ซ.เลียบคลองภาษีเจริญฝั่งเหนือ 12 แขวงหนองแขม
เขตหนองแขม กรุงเทพฯ 10160

E-mail : sales@goodtimepack.com, goodtimepack@yahoo.co.th

www.goodtimepack.com, 02-8076461-9

